

1 . Product Name: White Meltblown

2 . Material and composition

Polypropylene 100%

3 . Specifications:

- ①. Product Style Meltblown/White
- ②. Basic weight 25G/m<sup>2</sup>
- ③. Width 0.165m/0.17m/0.175m/1.6m
- ④. Roll length: 450m/1600m/3100m

4. Physical Performance:

Item	Unit	Specification	Test Method	Note
Basic weight	gsm	26 $\geq$ 25 $\geq$ 24	GB/T 24218.1	Sample 100cm <sup>2</sup>
Tensile strength/MD	N/50mm	$\geq$ 6.5	GB/T 24218.3	200mm jaws separate width 50mm, jaws speed 100mm/min
Elongation/MD	%	$\geq$ 20	GB/T 24218.3	
Tensile strength/CD	N/50mm	$\geq$ 4	GB/T 24218.3	
Elongation/CD	%	$\geq$ 20	GB/T 24218.3	0.5kpa , 2500mm <sup>2</sup> , 10S/10 pieces , one layer
Thickness	mm		GB/T 24218.3	
Initial Efficiency	%	$\geq$ 95 $\geq$ 90	YY 0469-2011	For initial efficiency test, 0.3 $\mu$ m NaCl solid particle, the face flow Initial Pressure Pa $\leq$ 45 is 32L/min/TSI8130A
Initial Pressure	Pa	$\leq$ 45		

5. Packaging unit: According to customer requirements

6. Lifetime: 12 months

7. Storage and transport conditions (including temperature and humidity): Store in dry and ventilated environment.

During transportation, products shall not be contaminated and shall be strictly protected from rain and trampling.

8. Precautions, restrictions, warnings and / or special care: Avoid contact with moisture, moisture, fire and smoke. Avoid chemical contamination.